



Barrel Gauge Stainless Level One - Type B-SSR



Calibration: Consists of 3 pieces. Outer plastic piece, inner plastic piece, and a piece of paper in between.

Red Lock Nut: HDPE Plastic.

Bushing: Aluminum bushing, can be 2", 1.5", or .75"

HDPE Float: High Density Polyethylene Plastic. For 1.5 or 2 inch

Nitrophyll Float: For .75 inch.

Internal Rods: Stainless Steel 316

Part Number—
B-(Gallon Size)-(Size Opening)-(SSR)
Sample—B-55-.75-SSR

What it is:

Top mounted liquid level gauge that can measure the level of Drums & Barrels. Comes in 55 Gallon, 30 Gallon, and 15 Gallon Models. Can accommodate .75", 1.5", or 2" openings.

.75" has Nitrophyll Float, instead of the standard HDPE Float.

Additional Options:

Audible Alarm Accessory: This add on feature can turn your mechanical gauge into an audible Hi or Lo level alarm.

LED At-A-Glance Accessory: Another add on feature. This can give your mechanical gauge remote reading capability.

Gauge Guard: A cover that protects the exposed plastic components on top of the gauge.

Replacement Parts -

B-Kit - Replaces all of the gauge components from the red lock nut and up. Includes: Red HDPE Plastic Nut, Duro Nitrile Gasket, Plastic Cellulose acetate inner and outer calibration. (must state gallon size)

BG-Kit-ALN - Replaces all of the gauge components from the red lock nut and up with upgraded parts. Includes: Aluminum Lock Nut, Duro Nitrile Gasket, Plastic Cellulose acetate outer calibration, Glass inner calibration. (must state gallon size to order)

Instructions for Operation:

This gauge is a simple volume reading tool. The top of the red indicator is an indication of your approximate fuel level in your tank. Once installed, you simply view the calibration to monitor your tank level. Indicator is calibrated in eighths of a tank on one side, and quarters of a tank on the other.

Krueger Sentry Gauge
1873 Siesta Lane
Green Bay, WI 54313

www.ksentry.com



Contact us for more info or a local distributor:

Ph: 920-434-8860

Fax: 920-434-8897

Email: info@ksentry.com