



**KRUEGER
SENTRY
GAUGE®**

The Barrel Gauge (Plastic Model) - Type P55 Spec Sheet

Component:	Description
Calibration:	Consists of 3 pieces. Glass inner piece, plastic outer piece, and a calibrated piece of paper in between them.
Gasket:	Seals the gauge to the bushing. Standard material is Viton.
Bushing:	NPT male fitting that threads into your tank's female fitting. Standard material is PVC. Standard size is 2 inch. Optional .75" inch is available.
Gauge Guard	Gauge Guard tightens the calibration and the gauge to the bushing, and also protects the calibration from damage. Standard material is PVC.
Standard Rod:	Stationary 3/16" rod inside the tank, stabilizes the gauge. Standard material is Peek Plastic. Also available in Kynar plastic.
Push Rod:	Mobile 3/16" rod inside the tank, moves the red indicator up and down vertically. Standard material is Peek Plastic. Also available in Kynar plastic.
Float Rod:	Mobile 3/16" rod inside the tank, moves the push rod up and down vertically. Standard material is Peek Plastic. Also available in Kynar plastic.
Float:	Attached to the float rod inside the tank. Floats on top of the liquid. Standard material is HDPE Plastic.

Sample Part Number - P-55-2

P is the gauge type. 55 is the gallon size on the barrel. 2 is the fitting size.

Krueger Sentry Gauge
1873 Siesta Lane
Green Bay, WI 54313

www.ksentry.com



Contact us for more info
Ph: 920-434-8860
Fax: 920-434-8897

Email: info@ksentry.com