



All Plastic Direct Reading Gauge—Type PD



Calibration: Consists of 3 pieces. Outer plastic piece, inner plastic piece, and a piece of paper in between.

PVC Plastic Gauge Guard

Bushing: PVC bushing, can be 2" - 1.5" - or .75"

HDPE Float: High Density Polyethylene Plastic.

Internal Rods: Standard Construction is PEEK Plastic. Kynar Plastic is also available.

Part Number—
 PD-(size opening)-(tank depth)+(ext)-(list options)
 Sample—PD-2-48+12

What it is:

Top mounted liquid level gauge that can measure from 17 inches to 110 inches in depth. Bushing size can be 2", 1.5", or .75". Gauges are custom made in house to fit your tank. Can also accommodate for double walls and pipe risers.

Additional Options - Not included:

Audible Alarm Accessory: This add on feature can turn your mechanical gauge into an audible Hi or Lo level alarm.

LED At-A-Glance Accessory: Another add on feature. This can give your mechanical gauge remote reading capability.

Replacement Parts -

DG-Kit-VTN - Replaces all of the gauge components underneath the PVC Gauge Guard. Includes: Viton Gasket, Plastic Cellulose acetate outer calibration, Glass inner calibration, HDPE red indicator.

Instructions for Operation:

This gauge is a simple volume reading tool. The top of the red indicator is an indication of your approximate fuel level in your tank. Once installed, you simply view the calibration to monitor your tank level. Indicator is calibrated in eighths of a tank on one side, and quarters of a tank on the other.

Krueger Sentry Gauge
 1873 Siesta Lane
 Green Bay, WI 54313

www.ksentry.com



Contact us for more info:
 Ph: 920-434-8860
 Fax: 920-434-8897

Email: info@ksentry.com