KRUEGER SENTRY GAUGE
1873 SIESTA LANE GREEN BAY, WI 54313 | 920-434-8860 | www.ksentry.com

Barrel Gauge Stainless Level 2 – Type B-S2

Top mounted liquid level gauge that can measure the level of Drums & Barrels. Comes in 55 Gallon, 30 Gallon, and 15 Gallon Models. Can accommodate .75", 1.5", or 2" openings.



Calibration: Consists of 3 pieces –
Outer plastic piece, inner plastic piece, and a piece of paper in between.
Upgrades: Inner glass

Lock Nut: HDPE Plastic
Also available in aluminum or PVC.

Bushing: Aluminum
Can be 2", 1.5" or .75".

Float: 316 Stainless Steel

Internal Rods: 316 Stainless Steel
Non-Riveted Assembly

Part Number—
B-(Gallon Size)-(size opening)-(list options)-S2
Example: B-55-2-S2

Instructions for Operation:

The top of the red indicator is an indication of your approximate fuel level in your tank. Once installed, you simply view the calibration to monitor your tank level. Indicator is calibrated in eighths of a tank on one side, and quarters of a tank on the other as well as Gallons and Liters.

Installation Instructions available upon request

Replacement Parts –

Must specify gallon size when ordering

B-Kit - Replaces all the gauge components from the red lock nut and up. Includes: Red HDPE Plastic Nut, Duro Nitrile Gasket, Plastic Cellulose acetate inner and outer calibration.

BALN-Kit- Replaces all the top components with standard materials and an aluminum lock nut.

BG-Kit- Replaces all the top components with standard materials and a glass calibration.

BGALN-Kit - Replaces all the gauge components from the red lock nut and up with upgraded parts. Includes: Aluminum Lock Nut, Duro Nitrile Gasket, Plastic Cellulose acetate outer calibration, Glass inner calibration

Accessories & Add-ons:

- Gauge Guard: A cover that protects the exposed plastic components on top of the gauge.
- Audible Alarm: Can turn your mechanical gauge into an audible Hi or Lo level alarm.
- LED At-A-Glance: Can give your mechanical gauge remote reading capability.
- KSG SmartGauge Transmitter: Can convert a Krueger mechanical gauge into a digital output, 4-20mA, industry standard signal.