KRUEGER SENTRY GAUGE

1873 SIESTA LANE GREEN BAY, WI 54313 | 920-434-8860 | www.ksentry.com

At-A-Glance® Direct Reading Gauge – Type D UL Certified

Top mounted liquid level gauge that can measure from 6 inches to 144 inches in depth and withstand pressures up to 70 PSI. Bushing size can be 2", 1.5", or .75". Gauges are custom made in house to fit your tank. Can also accommodate for double walls and pipe risers.

UL CERTIFIED
SAFETY US·CA
MH27221



Calibration: Consists of 3 pieces –
Outer plastic piece, inner plastic piece, and a piece of paper in between.
Upgrades: Inner glass

Lock Nut: HDPE Plastic
Also available in aluminum.

Bushing: Aluminum
Can be 2", 1.5" or .75".

Float: HDPE
Also available in Nitrophyll.

Internal Rods: Standard construction is galvanized steel rods with brass rivets.
Additional options are stainless steel rods

Part Number—
D-(size opening)-(tank depth)+(ext)-(list options)
Example: D-2-48+12

Material Options and Limitations:

- All Bushing sizes available: .75'', 1.5'', and 2''
- Standard Direct Reading Gauge-Type D-Rods are galvanized steel, floats are HDPE plastic, bushing is aluminum, calibration top is plastic.
- Stainless Level One-Type D-S1- Rods become stainless.

**The Stainless Level Two – S2 and All Plastic – PD materials are not UL approved*

Add-Ons and Limitations:

- Inner glass
- Aluminum Lock Nut
- Nitrophyll Float

**Solid Glass, PVC nut, PVG and ALG guards are not UL approved*

Instructions for Operation:

This gauge is a simple volume reading tool. The top of the red indicator is an indication of your approximate fuel level in your tank. Once installed, you simply view the calibration to monitor your tank level. Indicator is calibrated in eighths of a tank on one side, and quarters of a tank on the other.

Installation Instructions available upon request