KRUEGER SENTRY GAUGE
1873 SIESTA LANE GREEN BAY, WI 54313 | 920-434-8860 | www.ksentry.com

Therma Gauge – Type H

Top mounted liquid level gauge that can measure from 6 inches to 144 inches in depth. Bushing sizes can be 2" or 1.5". Gauges are custom made in house to fit your tank. Can also accommodate for double walls and pipe risers. The Type H Gauge has a 2-piece bushing construction that allows you to aim your swing arm away from walls, corners, and other obstructions.



Calibration: Cellulose Acetate
Consists of 3 pieces –
Outer plastic piece, inner plastic piece, and a piece of paper in between.
Upgrades: Inner glass and Solid Glass

Lock Nut: HDPE Plastic
Upgrades: Aluminum and PVC

Bushing: Aluminum
Can be 2", 1.5".
Upgrades: PVC and Stainless steel

Thermallwell:

Float: HDPE
Upgrades: Stainless Steel and Nitrophyll.

Internal Rods: Galvanized steel rods with brass rivets.
Additional options are stainless steel rods, peek rods, or Kynar (PVDF) rods.

Other Materials:
Indicator is HDPE
Gasket is Duro Nitrile (Upgrade: Viton)

Part Number—
H-(size opening)-(tank depth)+(ext)-(list options)
Example: H-2-48+12

Instructions for Operation:

This gauge is a simple volume reading tool. The top of the red indicator is an indication of your approximate fuel level in your tank. Once installed, you simply view the calibration to monitor your tank level.
Indicator is calibrated in eighths of a tank on one side, and quarters of a tank on the other.

Installation Instructions available upon request

Material Options:

- **Standard Therma Gauge**-Type H-Rods are galvanized steel, floats are HDPE plastic, bushing is aluminum, calibration top is plastic.
- **Stainless Level One**-Type H-S1- Rods become stainless.
- **Stainless Level Two**-Type -H-S2- Rods and floats become stainless.
- **Stainless Level Three**-Type H-S3- This model comes standard with Glass Calibration, Aluminum Locking Nut, Stainless Steel Bushing, Stainless Steel Rods, and Stainless Steel Floats.
- **All Plastic Model**—Type PH—This model comes standard with Glass Calibration, PVC Gauge Guard, PVC Bushing, PEEK Plastic Rods, HDPE Plastic Float.

Accessories & Add-ons:

- Gauge Guard: A cover that protects the exposed plastic components on top of the gauge.
- Audible Alarm: Can turn your mechanical gauge into an audible Hi or Lo level alarm.
- LED At-A-Glance: Can give your mechanical gauge remote reading capability.
- KSG SmartGauge Transmitter: Can convert a Krueger mechanical gauge into a digital output, 4-20mA, industry standard signal.