KRUEGER SENTRY GAUGE
1873 SIESTA LANE GREEN BAY, WI 54313 | 920-434-8860 | www.ksentry.com

Therma Gauge Stainless Level 1 – Type H-S1

Top mounted liquid level gauge that can measure from 6 inches to 144 inches in depth. Bushing sizes can be 2" or 1.5". Gauges are custom made in house to fit your tank. Can also accommodate for double walls and pipe risers. The Type H Gauge has a 2-piece bushing construction that allows you to aim your swing arm away from walls, corners, and other obstructions.



Calibration: Cellulose Acetate
Consists of 3 pieces –
Outer plastic piece, inner plastic piece, and a piece of paper in between.
Upgrades: Inner glass and Solid Glass

Lock Nut: HDPE Plastic
Upgrades: Aluminum and PVC

Bushing: Aluminum
Can be 2", 1.5".
Upgrades: PVC and Stainless steel

Thermallwell:

Float: HDPE
Upgrades: Stainless Steel and Nitrophyll.

Internal Rods: 316 Stainless Steel Non-Riveted Assembly.

Other Materials:
Indicator is HDPE
Gasket is Duro Nitrile (Upgrade: Viton)

Part Number—
H-(size opening)-(tank depth)+(ext)-(S1)
Example: H-2-48+12-S1

Instructions for Operation:

This gauge is a simple volume reading tool. The top of the red indicator is an indication of your approximate fuel level in your tank. Once installed, you simply view the calibration to monitor your tank level.
Indicator is calibrated in eighths of a tank on one side, and quarters of a tank on the other.

Installation Instructions available upon request

Accessories & Add-ons:

- Gauge Guard: A cover that protects the exposed plastic components on top of the gauge.
- Audible Alarm: Can turn your mechanical gauge into an audible Hi or Lo level alarm.
- LED At-A-Glance: Can give your mechanical gauge remote reading capability.
- KSG SmartGauge Transmitter: Can convert a Krueger mechanical gauge into a digital output, 4-20mA, industry standard signal.

Replacement Parts:

Replaces all components from the lock nut and up.

H-Kit - Includes: Red HDPE Plastic Nut, Duro Nitrile Gasket, Plastic Cellulose acetate inner and outer calibration.
HGALN-Kit - Includes: Aluminum Lock Nut, Duro Nitrile Gasket, Plastic Cellulose acetate outer calibration, Glass inner calibration.
HSG-Kit – Includes: Solid Glass Calibration, Indicator Disc, Duro Nitrile Gasket, and Aluminum Lock Nut