KRUEGER SENTRY GAUGE
1873 SIESTA LANE GREEN BAY, WI 54313 | 920-434-8860 | www.ksentry.com

Leak Gauge – Type K

Top mounted liquid leak gauge that can measure from 6 inches to 170 inches in depth. Bushing size can be 2" or 1.5". Gauges are custom made in house to fit your tank. This gauge is designed to monitor either the interstitial space of a double wall containment system, or it can mount into an external monitoring pipe.



Calibration: Consists of 3 pieces –
Outer plastic piece, inner plastic piece, and a piece of paper in between.
Upgrades: Inner glass or Solid Glass

Lock Nut: HDPE Plastic
Also available in aluminum or PVC.

Bushing: Aluminum
Can be 2", 1.5".
Stainless steel options also available

Internal Rods: Standard construction is Aluminum

Union: Compression union

Float: HDPE

Part Number—
K-(size opening)-(tank depth)-(list options)
Example: K-2-48

Environmental Protection – FDEP EQ 675

The Leak gauge is officially approved for use in double wall containment systems by several state environmental protection agencies.

· Florida DEP
· Michigan DEP

Approval letters can be found on the Leak Gauge page of our website.

Material Options:

Internal Rods are limited to standard construction

.75'' Busing available up to 76'' tank depth

Accessories & Add-ons:

- Gauge Guard: A cover that protects the exposed plastic components on top of the gauge.

- Audible Alarm: Can turn your mechanical gauge into an audible Leak alarm.

Instructions for Operation:

This gauge is a simple visual tool. If the red indicator rises into the viewing window, it is indicating that there is a leak occurring in your double wall containment system. Once installed, you simply view the calibration to monitor your interstitial space. The indicator is not calibrated. It simply indicates leak or no leak.