KRUEGER SENTRY GAUGE
1873 SIESTA LANE GREEN BAY, WI 54313 | 920-434-8860 | www.ksentry.com

All Plastic Therma Gauge – Type PH

Top mounted liquid level gauge that can measure from 6 inches to 144 inches in depth and withstand pressures up to 70 PSI. Bushing size can be 2", 1.5", or .75". Gauges are custom made in house to fit your tank. Can also accommodate for double walls and pipe risers.



Calibration: Cellulose Acetate
Consists of 3 pieces –
Outer plastic piece, inner **glass** piece, and a piece of paper in between.
Upgrades: Solid Glass

PVC Gauge Guard

Bushing: PVC
Can be 2" and 1.5"

Thermallwell: PVC

Float: HDPE

Internal Rods: Peek Plastic
Also available in PVDF – Kynar
HDPE Rivets

Other Materials:
Indicator is HDPE
Gasket is Duro Nitrile (Upgrade: Viton)

Part Number—
PH-(size opening)-(tank depth)+(ext)-(list options)
Example: PH-2-48+12

Instructions for Operation:

This gauge is a simple volume reading tool. The top of the red indicator is an indication of your approximate fuel level in your tank. Once installed, you simply view the calibration to monitor your tank level. Indicator is calibrated in eighths of a tank on one side, and quarters of a tank on the other.

Installation Instructions available upon request

Accessories & Add-ons:

- Gauge Guard: A cover that protects the exposed plastic components on top of the gauge.
- Audible Alarm: Can turn your mechanical gauge into an audible Hi or Lo level alarm.
- LED At-A-Glance: Can give your mechanical gauge remote reading capability.
- KSG SmartGauge Transmitter: Can convert a Krueger mechanical gauge into a digital output, 4-20mA, industry standard signal.

Replacement Parts:

HG-Kit-VTN - Replaces all of the gauge components underneath the PVC Gauge Guard. Includes: Viton Gasket, Plastic Cellulose acetate outer calibration, Glass inner calibration, HDPE red indicator.