



KRUEGER SENTRY GAUGE®

Direct Reading Gauge —Type D



Calibration: Consists of 3 pieces. Outer plastic piece, inner plastic piece, and a piece of paper in between. Optional glass inner piece is available.

Red Lock Nut: HDPE Plastic. Also available in aluminum or PVC.

Bushing: Aluminum bushing, can be 2", 1.5" or .75". Special package allows for a PVC Bushing also.

HDPE Float: Also available in Stainless Steel or Nitrophyll.

Internal Rods: Standard construction is galvanized steel rods with brass rivets. Optional stainless steel rods, peek rods, or kynar rods are available.

Part Number—
D-(size opening)-(tank depth)+(ext)-(list options)
Sample—D-2-48+12

What it is:

Top mounted liquid level gauge that can measure from 6 inches to 144 inches in depth. Bushing size can be 2", 1.5" or .75". Gauges are custom made in house to fit your tank. Can also accommodate for double walls and pipe risers.

Additional Options:

Audible Alarm Accessory: This add on feature can turn your mechanical gauge into an audible Hi or Lo level alarm.

LED At-A-Glance Accessory: Another add on feature. This can give your mechanical gauge remote reading capability.

Gauge Guard: A cover that protects the exposed plastic components on top of the gauge.

Material Choices and Limitations:

Standard choices are listed on picture to the left.

Stainless Steel Floats: Maximum tank depth is reduced to 120 inches.

Plastic Rods: Maximum tank depth is reduced to 110 inches.

Material Packages / Gauge Packages:

- **Standard Direct Reading Gauge-Type D-** Rods are galvanized steel, floats are HDPE plastic, bushing is aluminum, calibration top is plastic.
- **Stainless Level One-Type D-S1-** Rods become stainless.
- **Stainless Level Two-Type -D-S2-** Rods and floats become stainless.
- **All Plastic Model—Type PD—**This model comes standard with Glass Calibration, PVC Gauge Guard, PVC Bushing, PEEK Plastic Rods, HDPE Plastic Float.

Krueger Sentry Gauge
1873 Siesta Lane
Green Bay, WI 54313

www.ksentry.com



Contact us for more info or a local distributor:
Ph: 920-434-8860
Fax: 920-434-8897
Email: info@ksentry.com