




# KRUEGER SENTRY GAUGE

## The Overfill Gauge Stainless Level 2—Type OF-S2



Calibration: Consists of 3 pieces. Outer plastic piece, inner plastic piece, and a piece of paper in between.

Lock Nut: HDPE Plastic.

Bushing: Aluminum bushing, can be 2" or 1.5"

Internal Rods: Stainless steel

Float: Stainless Steel

Part Number—  
OF-(size opening)-(overfill warning level)-(list options)  
Sample—OF-2-8-S2

### What it is:

Top mounted pop up gauge that can measure from 6 inches to 76 inches in Length. Bushing size can be 2" or 1.5". Gauges are custom made in house to fit your application. Most Overfill Alert Gauges are between 6 inches and 12 inches. They are designed to pop up at a specific level (usually 90 percent) and warn you that the tank is almost full. Provides visual overfill warning.

### Additional Options:

**Audible Alarm Accessory:** This add on feature can turn your mechanical gauge into an audible Hi or Lo level alarm.

**Gauge Guard:** A cover that protects the exposed plastic components on top of the gauge.

### Material Choices and Limitations:

Standard choices are listed on picture to the left.

Some options such as stainless rods, stainless floats, and plastic rods will limit the sizes available.

### Replacement Parts

**OF-Kit** - Repair kit includes everything above the bushing all in original materials. Including the plastic calibration, plastic red lock nut, nitrile gaskets, and the red indicator.

**OFGALN-Kit**- Repair Kit includes everything above the bushing. Including the glass calibration, Aluminum locking nut, Viton gaskets, and the red indicator.

Krueger Sentry Gauge  
1873 Siesta Lane  
Green Bay, WI 54313

[www.ksentry.com](http://www.ksentry.com)



Contact us for more info or a local distributor:

Ph: 920-434-8860

Fax: 920-434-8897

Email: [info@ksentry.com](mailto:info@ksentry.com)